

SAFETY DATA SHEET



Jotun Mur Silikonemulsjon Maling, Silicone Emulsion Paint

1. Identification of the substance/preparation and company/undertaking

- Product name and/or code** : Jotun Mur Silikonemulsjon Maling, Silicone Emulsion Paint
- Supplier/Manufacturer** : Jotun Paints (Europe) Ltd.
Stather Road
Flixborough, Scunthorpe
North Lincolnshire
DN15 8RR
England
- Tel: +44 17 24 40 00 00
Fax: +44 17 24 40 01 00
- Emergency telephone number** : Contact National Poison Centre via Hospital or Registered Medical Practitioner
- Product use** : Coatings: Waterborne paint.

2. Composition/information on ingredients

Chemical name*	CAS no.	EC number	%	Classification
alkanes, c9-12-iso-	90622-57-4	292-459-0	1 - 2.5	R10 Xn; R65
4,5-dichloro-2-n-octyl-4-isothiazolin-3-one	64359-81-5	264-843-8	0 - 1	Xn; R21/22 C; R34 Xi; R37 R43 N; R50
See section 16 for the full text of the R-phrases declared above				

Occupational exposure limits, if available, are listed in section 8.

3. Hazards identification

The preparation is classified as dangerous according to Directive 1999/45/EC and its amendments.
May cause sensitisation by skin contact.



Irritant

4. First-aid measures

First-aid measures

- General** : In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Give nothing by mouth. If unconscious, place in recovery position and seek medical advice.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do not use solvents or thinners.
- Eye contact** : Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open.
- Ingestion** : If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do not induce vomiting.

5. Fire-fighting measures

- Extinguishing media** : Recommended: alcohol-resistant foam, CO₂, powders, water spray.
Not to be used : water jet.
- Recommendations** : Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard. Appropriate breathing apparatus may be required. Cool closed containers exposed to fire with water. Do not release runoff from fire to sewers or waterways.

6. Accidental release measures

- Personal precautions** : Avoid breathing vapour or mist. Refer to protective measures listed in sections 7 and 8.
- Spill** : Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Do not allow to enter drains or watercourses. Preferably clean with a detergent. Avoid using solvents. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.

Note: see section 8 for personal protective equipment and section 13 for waste disposal.

7. Handling and storage

- Handling** : Keep container tightly closed.
- Avoid contact with skin and eyes. Avoid inhalation of vapour, spray or mist.
- Eating, drinking and smoking should be prohibited in area where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking.
- Put on appropriate personal protective equipment (see section 8).
- Never use pressure to empty. Container is not a pressure vessel. Always keep in containers made from the same material as the original one.
- Comply with the health and safety at work laws.
- When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits.
- Storage** : Store in accordance with local regulations. Must be stored in a dry location. Keep container in a well-ventilated place. Keep away from: oxidising agents, strong alkalis, strong acids.
No smoking. Prevent unauthorised access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.
Do not empty into drains..

8. Exposure controls/personal protection

- Engineering measures** : Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction.
- Personal protective equipment**
- Respiratory system** : If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. By spraying : particulate filter(P2). In confined spaces, use compressed-air or fresh-air respiratory equipment.
- Hands** : For prolonged or repeated handling, use gloves: neoprene or nitrile.
- Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.
For right choice of glove materials, with focus on chemical resistance and time of penetration, seek advice by the supplier of chemical resistant gloves.
- Eyes** : Use safety eyewear designed to protect against splash of liquids.

9. Physical and chemical properties

- Physical state** : Liquid.
- Odour** : Characteristic.
- Colour** : Various colours.
- Density** : 1.5 g/cm³
- Solubility** : Easily soluble in cold water, hot water.

10. Stability and reactivity

Stable under recommended storage and handling conditions (see section 7).

Hazardous decomposition products: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.

Thermal decomposition (>200°C) may liberate anhydrides and relatively low concentrations of isocyanates.

11. Toxicological information

There is no data available on the preparation itself. The preparation is not classified as dangerous according to Directive 1999/45/EC and its amendments.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin. If splashed in the eyes, the liquid may cause irritation and reversible damage.

Contains (4,5-dichloro-2-n-octyl-4-isothiazolin-3-one). May produce an allergic reaction.

12. Ecological information

There is no data available on the preparation itself.

Do not allow to enter drains or watercourses.

The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and is not classified as dangerous for the environment, but contains substance(s) dangerous for the environment. See section 2 for details.

Ecotoxicity data

<u>Ingredient name</u>	<u>Species</u>	<u>Period</u>	<u>Result</u>
4,5-dichloro-2-n-octyl-4-isothiazolin-3-one	Daphnia magna (EC50)	48 hour/hours	0.00522 mg/l
	Daphnia magna (EC50)	48 hour/hours	0.00751 mg/l
	Daphnia magna (EC50)	48 hour/hours	0.0301 mg/l
	Oncorhynchus mykiss (LC50)	96 hour/hours	0.0027 mg/l
	Oncorhynchus mykiss (LC50)	96 hour/hours	0.0091 mg/l
	Oncorhynchus mykiss (LC50)	96 hour/hours	0.0104 mg/l

13. Disposal considerations

Do not allow to enter drains or watercourses. Material and/or container must be disposed of as hazardous waste.

European waste catalogue (EWC) : 08 01 11* waste paint and varnish containing organic solvents or other dangerous substances

14. Transport information

International transport regulations

Proper shipping name : -
UN Number : Not regulated.
Class : -
Sub-risk : -
Packing group : -
Label :

Additional information

ADR / RID : -
IMDG : Marine pollutant: No.

IATA : -

This preparation is not classified as dangerous according to international transport regulations (ADR/RID, IMDG or ICAO/IATA). Transport in accordance with ADR/RID, IMDG/IMO and ICAO/IATA and national regulation.

-

15. Regulatory information

EU regulations

Hazard symbol/symbols :



Irritant

Contains : 4,5-dichloro-2-n-octyl-4-isothiazolin-3-one
Risk phrases : R43- May cause sensitisation by skin contact.
Safety phrases : S2- Keep out of the reach of children.
S23- Do not breathe spray.
S24- Avoid contact with skin.
S37- Wear suitable gloves.
S46- If swallowed, seek medical advice immediately and show this container or label.
S51- Use only in well-ventilated areas.

16. Other information

CEPE Classification : 7
Full text of R-phrases referred to in sections 2 and 3 - United Kingdom (UK) : R10- Flammable.
R21/22- Harmful in contact with skin and if swallowed.
R65- Harmful: may cause lung damage if swallowed.
R34- Causes burns.
R37- Irritating to respiratory system.
R43- May cause sensitisation by skin contact.
R50- Very toxic to aquatic organisms.

Notice to reader

History

Date of printing : 16.02.2006.
Date of issue : 16.02.2006.
Version : 2
Prepared by : Jotun Group Product Safety Department

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.

Indicates information that has changed from previously issued version.

Version 2

Page: 4/4